

Technical Data – HBA400SP


Product description

- proprietary formulation of Fe and four other synthesised metals in a flake format layered and calendered with a special resin
- magnetic, conductive and thermal properties
- absorbs electro-magnetic waves, interference and converts the associated waves into heat

Construction

- Absorbing material
- Adhesive coating
- Paper liner

Technical data



Item	Unit		Spec.		Test method
Standard thickness	µm	inch	500	0.02	-
Permability (at 1 MHz)	µ'	-	37	-	-
Temperature range	°C	°F	-25~125	-13~257	-
Specific gravity	g/cm ³	-	2.5 ± 0.3	-	-
Tensile strength	kg/cm ²	lb/inch ²	>100	>645.16	-
Surface Electrical resistance (min)	Ω	-	1 x 10 ⁸	-	-
Thermal Conductivity	W/m-K	-	0.8±0.1	-	-
Elongation	%	-	≥60	-	-
Environment	RoHS Compliant, Halogen Free				

Application

There are a wide range of applications throughout the electronics industry, where EMI /RFI prevention is required, in metal electrical cabinets, between PCBs.

Note

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.



High Performance Tapes and Adhesive Products

1 Crucible Road, Phoenix Parkway, Corby, Northamptonshire NN17 5TS
 Telephone: +44 (0)1536 260022 Fax: +44 (0)1536 260044

email: sales@hi-bondtapes.co.uk
 www.hi-bondtapes.com

Company Registration No. 3985595

